

MOTOROLA DTA100U

DIGITAL TERMINAL ADAPTER

FEATURES

- Single 54 to 1002 MHz digital video tuner
- Digital video (64 QAM/256QAM)
- MPEG-2 and MPEG-4 digital standard definition and high-definition video decode
- Accelerated 2-D graphics
- Integrated graphical user interface
- On-screen diagnostics
- External high-efficiency power supply
- 8MB Flash, 128MB of RAM



TECHNICAL SPECIFICATIONS

STANDARD INTERFACES

- Power indicator
- IR remote control (default mode)
- RF4CE remote control

FRONT PANEL

- Power indicator
- IR remote control sensor (XMP-1)

REAR PANEL

- F - connector for cable input
- RF Remod output
- HDMI output
- Hardware switch for Remod Ch. 3/4 selection
- Power input for external power supply

RF INPUT FREQUENCY

- 54 to 1002 MHz

GRAPHICS RESOLUTION

- 720 x 1280 maximum

VIDEO RESOLUTION

- 480i NTSC, 480p, 720p, 1080i

OPERATING TEMPERATURE

- 32° to 122°F (0° to 50°C)

OPERATING HUMIDITY

- 5 to 95% (non-condensing)

AC VOLTAGE

- 90 to 135 VAC, 57-63 Hz for North America operation

POWER DISSIPATION

- 4.75W AC

DIGITAL INPUT LEVEL

- 64 QAM (-15 to 15 dBmv)
- 256 QAM (-12 to 15 dBmv)

DIMENSIONS

- 1.0 x 4.4 x 2.8 (H x W x D)

WEIGHT

- 0.3 lbs.